

Boomlift / Manlift

Used Boom Lift Massachusetts - In terms of popular aerial machinery, the boom lift is one of the most recognizable. Boom lifts go by numerous names including cherry pickers, elevating work platforms, aerial platforms, aerial devices and mobile elevating work platforms; created to conduct jobs at higher elevations. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Workers need to remain safe as they access locations at higher altitudes. There is a wide variety of boom lift models to choose from. Most boom lifts can be successfully run with a single operator. This machine is popular for harvesting fruit in locations such as orchards that historically relied on climbing dangerous ladders. It can be difficult to secure a ladder on farmland or in orchard settings. Relying on a boom lift is an easier and safer way to reach tree tops. Gaining Access Over Obstacles Certain boom lifts are designed to move up and over items. This makes working over obstacles possible Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. Articulated boom lifts are comprised of many joints that allow the machine to bend under or over obstacles. The articulated boom sections can move independently to grant operators access to many locations. Articulated booms feature a tight turning radius, making them ideal for hallways and narrow storage corridors. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. Articulated boom lifts are utilized commonly for working on overhead power lines and wires. Certain models are outfitted with water cannons to be used in firefighting applications. Telescoping sections are available on certain models to extend reach to the maximum. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. The nickname "spiders" has been given to these boom lifts due to their legs which can support the machine on rough or steep terrain. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Electric models are preferred in interior situations due to the danger that carbon monoxide exhaust poses and how much quieter these models are. Telescopic Boom Lifts Articulating boom lifts and telescopic boom lifts move differently from each other. These units use hydraulics to retract and extend outwards and upwards. The worker who is in the platform has the controls to extend the lift and is able to operate without a second worker. Certain larger and taller models feature a jib located close to the top similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Certain boom lift models have a jib or an extension located between the platform and the end of the main boom. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Jibs are an option on many telescoping and articulating boom lifts. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts A popular type of articulating boom lift manufactured on the market is the Genie Z-boom Model. Designed to provide the most versatility in difficult to access spaces, this model has the capacity to lift up, over and out with superior positioning. The first Genie Z-30/20 articulating Z-boom model was launched in 1985. Thanks to their "up an over" abilities, they have gained the ultimate popularity that continues today. Proper Safety Measures Of course, safety is the highest priority when operating any type of boom lift. Safety hazards must be advertised to everyone

who is working in the area for best practices. Safely operating the equipment is a top priority for the operator and everyone in the working environment. Before starting the boom lift, it is paramount that the proper safety gear and communication is in place. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. Have a properly mounted, accessible and visible fire extinguisher mounted within reach. Maintaining a clear area around charging stations and work surfaces is important as tools or clutter could damage the boom lift or cause tire punctures etc. Daily Maintenance It is important to conduct a visual inspection prior to operating and to consult the maintenance manual to ensure everything is up to date. Lifting and supportive devices need to stabilize the weight on hand. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Safety can be increased with proper lighting and adequate ventilation along workbenches and within workshops and garages. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Some of the maintenance categories for the boom lift include the Engine, Platform, Controls and Function, Turntable, Booms and Drive Chassis. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. The maintenance inspection report is an essential component to keeping the machine operable and the staff safe while extending the service life and overall performance of the machine. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. Annual and Quarterly maintenance procedures need to be performed once or multiple times a year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Set yourself up for success by consulting your maintenance manual before operating the equipment to ensure battery life, oil changes and fluid levels are ready to go.